

Connectpoint® 42"

42" Digital Real Time Display

Connectpoint's newest generation of large ePaper displays have rugged protection, enhanced energy management and superb clarity. The CP-42 offers a customizable presentation of visual mapping, real-time departures, custom messaging, and optional advertising. This display can be either AC or solar-powered and mounted to a shelter frame or enclosed in a freestanding totem.

The CP-42 has been tested for extreme weather and outdoor use and offers a high-resolution ePaper screen with crisp daytime and nighttime visibility. The system's power and content are remotely managed by its cloud-based Connectpoint Asset Management System (CPAM™) from the convenience of a desktop or mobile device.



CP 42 Specifications

Active Area	42 inches
Dimensions	38"H x 28"W x 2"D
Weight	49 lbs
Resolution	2880 x 2160
Orientation	Landscape or Portrait
Screen Protection	2 layered: 3mm Tempered and 2mm Gorilla Glass 3 (anti-glare & UV stability) / IK07
Viewing Angle	Ultra-Wide 160°
Screen Color	16 level Greyscale Monochrome
Screen Illumination	Direct Light Guide
Connectivity	Wireless Cellular (4G) or WiFi or Ethernet
Operating Temperature	-20°C to 60°C
IP Rating	IP 66
Text-to-Speech	TTS capable with audio button option
Power Requirements	Ultra Low Power 12 v, Solar/LiFePo Battery, 110v Adapter
Installation Applications	Shelter, Wall, Totem, Kiosk, Custom Build

Ordering Matrix

Code	Model	Power Source	SIM Provider	Connection Type	Orientation	Text to Speech
CP	42	DC (Solar)	CS (Connectpoint)	C (Cellular Wireless) W (WIFI)	P (Portrait) L (Landscape)	Optional
Example: CP-42-DC-CS-C-P-B						