


## Connectpoint® 32"

### 32" Digital Real-Time Display

Connectpoint's newest generation of large ePaper displays have rugged protection, enhanced energy management and superb clarity. The CP-32 offers a customizable presentation of visual mapping, real-time departures, custom messaging, and optional advertising. This display can be either AC or solar-powered and mounted to a shelter frame or enclosed in a freestanding totem.



The CP-32 has been tested for extreme weather and outdoor use and offers a high-resolution ePaper screen with crisp daytime visibility. The system's power and content are remotely managed by its cloud-based Connectpoint Asset Management System (CPAM™) from the convenience of a desktop or mobile device.

### CP 32 Specifications

Active Area	32 inches
Dimensions	30.7" H x 18.8" W x 1.5" D
Weight	32 lbs.
Resolution	2560 x 1440
Orientation	Landscape or Portrait
Screen Protection	2 layer: 3mm Tempered and 2mm Gorilla Glass 3 (anti-glare & UV stability) / IK07
Viewing Angle	Ultra-Wide 160°
Screen Color	16 level Greyscale Monochrome
Screen illumination	Direct Light Guide
Connectivity	Wireless Cellular (4G), W-Fi or Ethernet
Operating Temperature	-20°C to 60°C
IP Rating	IP 66
Text-to-Speech	TTS capable with audio button option
Power Requirements	Ultra Low Power 12 v, Solar/LiFePo Battery, 110v Adapter
Installation Applications	Shelter, Wall, Totem, Kiosk, Custom Build

### Ordering Matrix

Code	Model	Power Source	SIM Provider	Connection Type	Orientation	Text to Speech
CP	32	AC (Electric)	CS (Connectpoint)	C (Cellular Wireless)	P (Portrait)	Optional
		DC (Solar)		W (WIFI)	L (Landscape)	
				E (Ethernet)		
Example: CP-32-DC-CS-C-P-B						